A Semi-Annual Technical Report February 1, 1995 - July 31, 1995

ANALYSIS AND CHARACTERIZATION OF GaN BASED MATERIALS AND DEVICES

Submitted to:

Dr. Max N. Yoder Electronics Division Code ONR-312, Room 607 Office of Naval Research 800 N. Quincy Street Arlington, VA 22217-5660

Submitted by:

Michael Shur John Marshall Money Professor

Approved for public released

Distribution Unbimited

SEAS Report No. UVA/525497/EE96/101 August 1995

DEPARTMENT OF ELECTRICAL ENGINEERING

REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1294, Arlington, VA 22202-4302, and to the Office of

Management and Budget, Paperwork Reductio	n Project (0704-0188), Washington, DC 20503.			
1. AGENCY USE ONLY (Leave blank)		,	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED
			July 1995	Semi-annual Technical 2/1/95 - 7/31/95
4. TITLE AND SUBTITLE Analysis and Characterization of GaN Based Materials and Devices		5. FUNDING NUMBERS Grant No. N00014-94-1-1011		
6. AUTHORS(S) Michael Shur, John Marshall Money Professor				
7. PERFORMING ORGANIZATION NAMES(S) AND ADDRESS(ES) University of Virginia Department of Electrical Engineering School of Engineering and Applied Science Thornton Hall Charlottesville, VA 22903-2442			8. PERFORMING ORGANIZATION REPORT NUMBER UVA/525497/EE96/101	
9. SPONSORING/MONITORING AGENCY NAMES(S) AND ADDRESS(ES) Office of Naval Research 800 North Quincy Street Arlington, VA 22217-5660			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT On limited			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)				
We calculated the elastic strain relaxation in wurtzite GaN-A1N-GaN semiconductor-insulator-semiconductor (SIS structures, Elastic strain tensor components, elastic energy, the density of the misfit dislocations, and the other parameters of the system were obtained as functions of the A1N layer thickness. Theoretical values of the elastic strain relaxation are in satisfactory agreement with experimental data extracted from capacitance-voltage characteristics of GaN-A1N-Gun SIS structures.				
Approved to: public telegred Diographysiss				
14. SUBJECT TERMS			15. NUMBER OF PAGES 4	
gallium nitride, aluminum nitride, semiconductor-insulator-semiconductor structures, elastic strain relaxation, misfit dislocations			7	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURI OF ABST	TY CLASSIFICATION RACT	20. LIMITATION OF ABSTRACT
Unclassified	Unclassified	Unclassified Unlimited		Unlimited
VON 7540 AV 380 550A				Standard Form 208 (800104 Draft)

We calculated the elastic strain relaxation in wurtzite GaN-AIN-GaN semiconductor-insulator-semiconductor (SIS) structures.¹ Elastic strain tensor components, elastic energy, the density of the misfit dislocations, and the other parameters of the system were obtained as functions of the AlN layer thickness. Theoretical values of the elastic strain relaxation are in satisfactory agreement with experimental data extracted from the capacitance-voltage (C-V) characteristics of GaN-AlN-GaN SIS structures.² The calculated value of the starting point for the generation of dislocations is in agreement both with our experimental data and with the data³ obtained for GaN/AlN superlattices.

In Fig. 1, we plotted the relative deformation along the interface as a function of L calculated by considering the minimum of the energy of the system.¹




Fig. 1. Relative deformation along the interface as a function of AlN film thickness. Calculations: three $<11\overline{2}0>$ slip systems (thick solid line), two slip systems in the perpendicular directions (thin solid line), Ref. 5 (dashed-dotted line), Ref. 4 (dotted line). The experimental data extracted from the capacitance-voltage measurements (dashed line).

In this figure, we presented our theoretical results for the SIS structure with three

¹A. D. Bykhovski, B. L. Gelmont, and M. S. Shur. Elastic Strain Relaxation in GaN-AlN-GaN Semiconductor-Insulator-Semiconductor Structures, J. Appl. Phys., 1 September 1995, to be published.

²A. Bykhovski, B. Gelmont, M. Shur, and A. Khan, Inst. Phys. Conf. Ser. No 137: Chapter 7, 691 (1994). ³Z. Sitar, M. J. Paisley, B. Yan, J. Ruan, W. J. Choyke, and R. F. Davis, J. Vac. Sci. Technol. B 8, 316 (1990).

slip systems along the $<11\overline{2}0>$ directions, and for a structure having two slip systems in the perpendicular directions. We also showed in Fig. 1 the experimental data extracted from the capacitance-voltage measurements. ² Finally, for comparison, we plotted the results for an overlayer on the infinite substrate obtained in ^{4,5}. Ref. ⁵, predicts too strong a relaxation in thinner (up to 50 Å thick) AlN films (see Fig. 1). It predicts a starting point for the generation of dislocations at L = 5 - 7.5 Å (2-3 monolayers) which is clearly too small.^{2,3} More precise calculations for an overlayer on the infinite substrate made in ⁴ gives even a larger overestimation of the relaxation process. As it can be seen from Fig. 1, our approach gives the best fit to the experimental data, if the hexagonal slip systems are taken into account.

Our results confirm that the gradual relaxation process starts from 30 Å AlN film thickness. The uniform contributions to the elastic strain tensor components decrease by approximately an order of magnitude when the film thickness increases from 30 Å to 100 Å. Commensurate with this decrease is an increase in a non-uniform contribution of the misfit dislocations. The dislocation interactions lead to redistribution of dislocations within 30 Å - 60 Å range of AlN film thicknesses.¹

⁴J. H. van der Merwe, J. Appl. Phys., 34, 123 (1963).

⁵J. W. Matthews, J. Vac. Sci. Technol., 12, 126 (1975).

DISTRIBUTION LIST

1 - 3	Dr. Max N. Yoder Electronics Division Code ONR-312, Room 607 Office of Naval Research 800 N. Quincy Street Arlington, VA 22217-5660
4	Mr. Michael Karp, Administrative Contracting Officer Office of Naval Research Resident Representative 101 Marietta Street, Suite 2805 Atlanta, GA 30323-0008
5	Director Naval Research Laboratory Attention: Code 2627 Washington, DC 20375
6	Defense Technical Information Center, S47031 Building 5, Cameron Station Alexandria, VA 22304-6145
7 - 8	M. Shur
9 - 10	H. Earnhardt, Engineering Library
11	SEAS Preaward Research Administration
*	SEAS Postaward Research Administration

*Cover letter

JO#6550:ph